844-2075 CHROMA-CHEM®RAW UMBER

Specification: 000000139717 Revision Date: 05-08-2017

Version Number: 07

1. Identification

Product identifier 844-2075 CHROMA-CHEM®RAW UMBER

Other means of identification

SAP Specification 000000139717

Recommended use Non-aqueous colorant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Chromaflo Technologies Corporation Company

2600 Michigan Avenue

Ashtabula, OH, USA 44005-0816

Chromaflo Technologies Canada Canadian facility

235 Orenda Road

Brampton, Ontario, Canada L6T-1E6

US telephone 440-997-5137 905-451-3810 Canadian telephone

NA: EMERGENCY # (3E) 866-519-4752 GLOBAL: EMERG. # (3E) (+1) 760-476-3962

3E CONTRACT # 12154 334294 **3E ACCESS CODE**

613-996-6666 **CANADA: CANUTEC**

EMERGENCY NUMBER

Product Regulatory

Services

ehs americas@chromaflo.com

2. Hazard(s) identification

Category 3 Physical hazards Flammable liquids

Health hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Warning

Flammable liquid and vapor. **Hazard statement**

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

In case of fire: Use appropriate media to extinguish.

Store in a well-ventilated place. Keep cool. **Storage**

Material name: 844-2075 CHROMA-CHEM®RAW UMBER SDS US

Disposal

Hazard(s) not otherwise classified (HNOC)

Dispose of contents/container in accordance with local/regional/national/international regulations.

None known.

Supplemental information

If product is in liquid or paste form, hazards related to dust are not considered significant. But product may contain substances that could be potential hazards if caused to become airborne due to abrasive processes.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-methoxy-1-methylethyl acetate		108-65-6	20 - 40
Iron Oxide		1309-37-1	2.5 - 10
Calcium Carbonate		1317-65-3	1 - 2.5
Carbon black, amorphous		1333-86-4	1 - 2.5
Silica, crystalline (quartz)		14808-60-7	1 - 2.5
Other components below reportable	elevels		40 - 60

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contactTake off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Get medical attention if irritation develops and persists.

IngestionRinse mouth. Get medical attention if symptoms occur.Most importantDirect contact with eyes may cause temporary irritation.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

of ignition

Special protective equipment and precautions for firefighters

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Specific methods

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: 844-2075 CHROMA-CHEM®RAW UMBER
000000139717 Version #: 07 Revision date: 05-08-2017 Issue date: 06-02-2015

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

HO COULT THE TAIL TAIL TO A LONG CONTRACTOR OF ACAD ACCOUNT

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Contaminants (29 CFR 1910. Type	Value	Form
Calcium Carbonate (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
ŕ		15 mg/m3	Total dust.
Carbon black, amorphous (CAS 1333-86-4)	PEL	3.5 mg/m3	
Iron Oxide (CAS 1309-37-1)	PEL	10 mg/m3	Fume.
Silica, crystalline (quartz) (CAS 14808-60-7)	PEL	0.05 mg/m3	
US. OSHA Table Z-3 (29 CFR 1910.1	000)		
Components	Туре	Value	Form
Iron Oxide (CAS 1309-37-1)	TWA	5 mg/m3	Respirable fraction.
,		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Silica, crystalline (quartz) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
(6.16 . 1666 66 .)		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
Carbon black, amorphous (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Iron Oxide (CAS 1309-37-1)	TWA	5 mg/m3	Respirable fraction.
Silica, crystalline (quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to Chemi	cal Hazards		
Components	Туре	Value	Form
Calcium Carbonate (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Carbon black, amorphous (CAS 1333-86-4)	TWA	0.1 mg/m3	

Material name: 844-2075 CHROMA-CHEM®RAW UMBER

2017 Issue date: 06-02-2015 3 / 9

US. NIOSH: Pocket Guide to Chemical Hazards					
Components	Type	Value	Form		
Iron Oxide (CAS 1309-37-1)	TWA	5 mg/m3	Dust and fume.		
Silica, crystalline (quartz) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.		
US. AIHA Workplace Environment	al Exposure Level (WEEL) Gu	ıides			
Components	Туре	Value			
2-methoxy-1-methylethyl	TWA	50 ppm			

Biological limit values No biological exposure limits noted for the ingredient(s).

Occupational Exposure Limits are not relevant to the current physical form of the product. **Exposure guidelines**

US - California OELs: Skin designation

2-methoxy-1-methylethyl acetate (CAS 108-65-6) Can be absorbed through the skin.

Appropriate engineering

acetate (CAS 108-65-6)

Explosion-proof general and local exhaust ventilation.

controls

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing.

In case of insufficient ventilation, wear suitable respiratory equipment. Use a NIOSH/MSHA Respiratory protection

approved respirator if there is a risk of exposure to vapor/mist at levels exceeding the exposure

limits.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene When using do not smoke. Always observe good personal hygiene measures, such as washing considerations

after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Liquid. Paste.

Color Brown

Sweet ether-like odor. Odor

Odor threshold Not available. pН Not available. Melting point/freezing point Not available.

Initial boiling point and boiling

range

> 289.4 °F (> 143 °C)

116.0 °F (46.7 °C) Setaflash Flash point

Evaporation rate Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%) Vapor pressure Not available. Vapor density Not available.

1.14 Relative density

SDS US

000000139717 Version #: 07 Revision date: 05-08-2017 Issue date: 06-02-2015 Solubility(ies)

Solubility (water) Not available. Not available. Partition coefficient

(n-octanol/water)

Auto-ignition temperature Not available. Not available. **Decomposition temperature** Not available. **Viscosity**

Other information

Not explosive. **Explosive properties** Not oxidizing. Oxidizing properties

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. Chemical stability Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

No adverse effects due to inhalation are expected. Inhalation Skin contact No adverse effects due to skin contact are expected. Direct contact with eyes may cause temporary irritation. Eye contact

Expected to be a low ingestion hazard. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not known.

Components **Species Test Results**

Carbon black, amorphous (CAS 1333-86-4)

Acute Oral

LD50 Rat > 8000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation. Serious eye damage/eye

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon black, amorphous (CAS 1333-86-4) 2B Possibly carcinogenic to humans.

Iron Oxide (CAS 1309-37-1) 3 Not classifiable as to carcinogenicity to humans.

Silica, crystalline (quartz) (CAS 14808-60-7) 1 Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Silica, crystalline (quartz) (CAS 14808-60-7) Known To Be Human Carcinogen.

Material name: 844-2075 CHROMA-CHEM®RAW UMBER 000000139717 Version #: 07 Revision date: 05-08-2017 Issue date: 06-02-2015

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN1263

UN proper shipping name

Transport hazard class(es)

Paint related material

Class 3
Subsidiary risk Label(s) 3
Packing group III

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions B1, B52, IB3, T2, TP1, TP29

Packaging exceptions 150
Packaging non bulk 173
Packaging bulk 242

DOT BULK

BULK

UN number UN1263

UN proper shipping name Paint related material

Transport hazard class(es)

Class 3
Label(s) 3
Packing group III

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions B1, B52, IB3, T2, TP1, TP29

Packaging exceptions 150
Packaging non bulk 173
Packaging bulk 242

IATA

UN1263 **UN** number

Paint related material UN proper shipping name

Transport hazard class(es)

Class 3 Subsidiary risk **Packing group** Ш **Environmental hazards** No. 3L **ERG Code**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Allowed with restrictions. Cargo aircraft only

IMDG

UN1263 **UN** number

UN proper shipping name Transport hazard class(es) PAINT RELATED MATERIAL

Class 3 Subsidiary risk Packing group Ш

Environmental hazards

Marine pollutant No. F-E, S-E **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Not established.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT; DOT Bulk packaging type



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the US Hazard Communication Standard and the Canadian Hazardous Products Regulation.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

Inventory name

(SDWA)

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon black, amorphous (CAS 1333-86-4) Listed: February 21, 2003 Silica, crystalline (quartz) (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3,

subd. (a))

Carbon black, amorphous (CAS 1333-86-4) Silica, crystalline (quartz) (CAS 14808-60-7)

International Inventories

Country(s) or region

Country(s) or region	inventory name	On inventory (yes/no)
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Buerte Bice	Toxic Substances Control Act (TSCA) Inventory	Voc

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes Taiwan Toxic Chemicals Substances Control Act No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

 Issue date
 06-02-2015

 Revision date
 05-08-2017

Version # 07

000000139717 Version #: 07 Revision date: 05-08-2017 Issue date: 06-02-2015

On inventory (ves/ne)*

Disclaimer

The information contained herein is based on data believed to be reliable and the manufacturer disclaims any liability incurred from the use or reliance upon the same. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.

SDS US

000000139717 Version #: 07 Revision date: 05-08-2017 Issue date: 06-02-2015